



BW SERIES / BW 系列產品

KEY BENEFITS 產品優勢

- Miniature size
- Positive make and break with snap-action disc
- Competitive price
- Suitable for most impregnation processes
- 体积小
- 速动型双金属片，反应速度快
- 有竞争力的价格
- 防真空浸漆工艺

APPLICATION 應用範圍

- HID ballasts
- DC motor
- Battery packs
- Heating appliance
- Fractional Power Motor
- Transformer
- AC brushless motor and pump
- 金卤灯镇流器
- 直流马达
- 充电电池组
- 电加热器具
- 分马力电机
- 变压器
- 交流无刷马达和水泵



CERTIFICATIONS 認證

AGENCY	STANDARD NUMBER	APPLICATION
VDE	EN60730-2-2	Motor protection
UL	UL 2111	Motor protection

MAXIMUM CONTACT RATINGS 觸點最大容量 5000 cycles

VOLTAGE	CURRENT
250 VAC	8 amperes
250 VAC	5 amperes
115 VAC	8 amperes

BW SERIES COMPARISON BW系列對比

ITEM NO	CURRENT & VOLTAGE	CASE MATERIAL	OPEN TEMP. RANGE(°C)	CASE SIZE (MM)	LEAD WIRE
BW-ACM	250V/5A	Metal	50-160	20.0x7.4x3.8	50-105°C 1015AWG22 70mm 110-150°C 3135AWG22 70mm
BW-ACM	250V/8A	Metal	50-160	20.0x7.4x3.8	50-150°C 3135AWG20 70mm
BW-ACP	250V/5A	Plastic	50-130	20.0x8.0x4.2	50-105°C 1015AWG22 70mm 110-130°C 3135AWG22 70mm
BW-BCM	250V/5A	Metal	50-160	15x6.7x3.2	50-150°C 3135AWG22 70mm
BW-BCP	250V/5A	Plastic	50-130	15x7.2x3.8	50-130°C 3135AWG22 70mm
BW-CCM	250V/5A	Metal	45-160	15x5.8x3	45-125°C 3266AWG22 60mm 130-160°C 3135AWG22 60mm
BW-CCP	250V/5A	Plastic	45-130	15x6.1x3.2	3266AWG22 60mm

CODE SYSTEM 產品編號代碼圖

BW - X X X - X X °C

- ▶ Open Temperature 動作溫度
- ▶ M-metal case 鐵殼, P-plastic case 塑殼
- ▶ C-normally close 常閉型, O-normally open 常開型
- ▶ A-normal 大體積, B-small size 小體積, C-smallest size 最小體積
- ▶ Device No. 產品型號

OPEN TEMP & RESET TEMP 額定動作溫度和復位溫度圖

MODEL	OPEN TEMP(°C)	RESET TEMP(°C)	MODEL	OPEN TEMP(°C)	RESET TEMP(°C)
45	45 ± 5	≥ 33	105	105 ± 5	70 ± 15
50	50 ± 5	30 ± 8	110	110 ± 5	75 ± 15
55	55 ± 5	35 ± 10	115	115 ± 5	75 ± 15
60	60 ± 5	40 ± 10	120	120 ± 5	80 ± 15
65	65 ± 5	45 ± 10	125	125 ± 5	85 ± 15
70	70 ± 5	45 ± 15	130	130 ± 5	90 ± 15
75	75 ± 5	50 ± 15	135	135 ± 5	95 ± 15
80	80 ± 5	55 ± 15	140	140 ± 5	100 ± 15
85	85 ± 5	55 ± 15	145	145 ± 5	105 ± 15
90	90 ± 5	60 ± 15	150	150 ± 5	110 ± 15
95	95 ± 5	65 ± 15	155	155 ± 5	110 ± 15
100	100 ± 5	65 ± 15	160	160 ± 5	115 ± 15

Company add: 2nd floor NO.4 building, Qinghuafang, Xingye road, Panyu, Guangzhou, China

Tel: 86 20-34826856 Fax: 86 20-62351066 Ext. 802

E-mail: webmaster@thermtector.com Website: www.safitty.com www.thermtector.com

公司地址: 广州市番禺区南村镇兴业大道清华坊商业中心4栋2楼
电话: 86 20-34826856 传真: 86 20-62351066 ext: 802

邮箱: webmaster@thermtector.com

网站: www.safitty.com www.thermtector.com